

FORM PTO-1449		U.S. Department of Commerce Patent and Trademark Office		Atty. Docket No. FTS 920030230 US1		Application No. 10/707,690	
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Use several sheets if necessary)				Applicant Huiling ZHU et al.			
				Filing Date 01/05/2004		Group 2818	
U.S. PATENT DOCUMENTS							
EXAMINER INITIAL		DOCUMENT NUMBER	DATE	NAME	CLASS	SUBCLASS	FILING DATE IF APPROPRIATE
FOREIGN PATENT DOCUMENTS							
		DOCUMENT NUMBER	DATE	COUNTRY	CLASS	SUBCLASS	TRANSLATION YES NO
OTHER DOCUMENTS (Including Author, Title, Date, Pertinent Pages, Etc.)							
DV		G. Zhang, et al., "A New 'Mixed-Mode' Reliability Degradation Mechanism in Advanced Si and SiGe Bipolar Transistors." IEEE Transactions on Electron Devices, vol. 49, no. 12, December 2002, pp. 2151-56.					
		H.S. Momose, et al., "Temperature Dependence of Emitter-Base Reverse Stress Degradation and its Mechanism Analyzed by MOS Structures." 1989 IEEE, Paper 6.2, pp. 140-143.					
		C.J. Huang, et al., "Temperature Dependence and Post-Stress Recovery of Hot Electron Degradation Effects in Bipolar Transistors." IEEE 1991, Bipolar Circuits and Technology Meeting 7.5, pp. 170-173.					
		S.R. Sheng, et al., "Degradation and Recovery of SiGe HBTs Following Radiation and Hot-Carrier Stressing." pp. 14-15, 2002					
		Z. Yang, et al., "Avalanche Current Induced Hot Carrier Degradation in 200 GHz SiGe Heterojunction Bipolar Transistors." pp. 1-5, 2002					
		H. Li, et al., "Design of W-Band VCOs with High Output Power for Potential Application in 77 GHz Automotive Radar Systems." 2003, IEEE GaAs Digest, pp. 263-66.					
		H. Wurzer, et al., "Annealing of Degraded non-Transistors-Mechanisms and Modeling." IEEE Transactions on Electron Devices, vol. 41, no. 4, April 1994, pp. 533-38.					
		B. Doyle, et al., "Recovery of Hot-Carrier Damage in Reoxidized Nitrided Oxide MOSFETs." IEEE Electron Device Letters, vol. 13, no. 1, January 1992, pp. 38-40					
		H.S. Momose, et al. "Analysis of the Temperature Dependence of Hot-Carrier-Induced Degradation in Bipolar Transistors for Bi-CMOS." IEEE Transactions on Electron Devices, vol. 41, no. 6, June 1994, pp. 978-987.					
		M. Khater, et al., "SiGe HBT Technology with $F_{max}/F_t = 350/300$ GHz and Gate Delay Below 3.3 ps". 2004 IEEE, 4 pages.					
		J.C. Bean, et al., "GEx Si 1-x/Si Strained-Layer Superlattice Grown by Molecular Beam Epitaxy". J. Vac. Sci. Technol. A 2(2), Apr.-June 1984, pp. 436-440.					
		J.H. Van Der Merwe, "Regular Articles". Journal of Applied Physics, Volume 34, No. 1, January 1963, pp. 117-122.					
		J.W. Matthews, et al., "Defects in Epitaxial Multilayers". Journal of Crystal Growth 27 (1974), pp. 118-125.					
		Subramanian S. Iyer, et al. " Heterojunction Bipolar Transistors Using Si-Ge Alloys". IEEE Transactions on Electron Devices, Vol. 36, No. 10, October 1989, pp. 2043-2064					
		R.H.M. Van De Leur, et al., "Critical Thickness for Pseudomorphic Growth of Si/Ge Alloys and Superlattices". J. Appl. Phys. 64 (6), 15 September 1988, pp. 3043-3050					
		D.C. Houghton, et al., "Equilibrium Critical Thickness for Si 1-x GEx Strained Layers on (100) Si". Appl. Phys. Lett. 56 (5), 29 January 1990, pp. 460-462					
DV		Q. Quyang et al., "Two-Dimensional Bandgap Engineering in a Novel Si/SiGe pMOSFET with Enhanced Device Performance and Scalability". 2000, IEEE, pp. 151-154.					
EXAMINER <i>Shuland</i>				DATE CONSIDERED 09/15/06			
*EXAMINER: Initial if citation considered, whether or not citation is in conformance with MPEP 609; draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant.							